



## MAINTENANCE OIL

Ideal for refreshing and maintaining Polyx®-Oil surfaces.



3079 Clear  
Matt



3081 Clear  
Satin



3098 Clear  
Semi-Matt/  
Anti-Slip (R9)



3440 White  
Transparent



### PRODUCT DESCRIPTION

Clear or transparent, fast drying wood finish for the basic care and maintenance of oiled/waxed wooden floors. Dull and matt flooring is refreshed with Osmo Maintenance Oil. By applying Maintenance Oil at the right time, time-consuming sanding works and renovation can be avoided. Also suitable for changing the gloss level of intact surfaces treated with Osmo Polyx®-Oil.

Suitable for wood; microporous surface does not crack, peel, flake or blister. Resistant to wine, beer, cola, coffee, tea, fruit juice, milk and water according to DIN 68861-1A – no water spots. When dry, finish is safe for humans, animals and plants and is suitable for children's toys as per EN 71.3 (European norm) and is resistant to saliva and perspiration according to DIN 53160 (German industrial norm).

### RECOMMENDED USE

Osmo Maintenance Oil is ideal for maintaining all wooden flooring treated with Polyx®-Oil, such as solid wood and plankwood flooring, parquet, blockstrip, OSB and cork flooring, as well as stairs and furniture. Highly recommended for public spaces (e.g. restaurants, museums and other high traffic floors).

### INGREDIENTS

Based on natural plant oils and waxes (sunflower oil, soya oil, thistle oil, carnauba wax and candelilla wax), paraffin, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Deaeromatized white spirit (benzene-free). VOC classification in compliance with EU regulations (2004/42/EC): out of scope.

Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.85-0.95 g/cm<sup>3</sup>  
Viscosity: 40-60s DIN 53211/3 mm  
Odour: faint/mild, after drying odourless  
Flash point: >60°C acc. DIN EN ISO 2719

### STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

### SURFACE PREPARATION

Wood surface must be clean, dry (moisture content max. 18 %) and free of dust.

Osmo Maintenance Oil is ready to use, please do not thin. Shake well before use.

Clean the surface thoroughly with Osmo Intensive Cleaner and rinse (damp mopping) with clear water.

The finished surface is influenced by several factors, including the wood's natural characteristics. Therefore, a trial application is always required, especially for unfamiliar surfaces.

### METHODS OF APPLICATION

Apply thinly and evenly to the clean and dry wood along the wood grain with Osmo Double Blade Scraper or Osmo Microfibre Roller, and massage into the wood with a white pad (do not massage in 3098). Remove excess product.

For smaller areas, Osmo Maintenance Oil can be applied with a lint-free cloth.

Allow for good ventilation while drying.

### CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).



## DRYING TIME

Approx. 3-4 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying.

## COVERAGE

1 litre covers approx. 40-60 m<sup>2</sup> with one coat. Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to reduced coverage.

## NOTE

The maintenance results are, among other things, influenced by the wood's natural characteristics. Therefore, a trial application is always required, especially for unfamiliar surfaces. When applying to raw or already greyed wood, the surface must be sanded and treated with Osmo Polyx<sup>®</sup>-Oil. Do not massage in Maintenance Oil 3098 Semi-Matt/Anti-Slip with a single disc machine.

## CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

3079 Clear Matt  
3081 Clear Satin  
3098 Clear Semi-Matt/Anti-Slip (R9)  
3440 White Transparent

## CAN SIZES

1 L; 2.50 L; 10 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 03/16



## WASH AND CARE

Highly effective special cleaning concentrate with natural ingredients – for regular cleaning and care!



8016  
Clear



### PRODUCT DESCRIPTION

Water-soluble cleaning concentrate for everyday cleaning and maintenance – especially developed for oiled and waxed wooden floors. It contains soaps based on natural oils. The wood does not dry out from cleaning. When used regularly, the highly effective Wash and Care produces a low-maintenance, non-slip surface. The water-soluble ingredients prevent streaks and do not form a layer. Especially mild on skin, free of dyes and aromas, biodegradable, free of solvents and emissions, and thus it supports a healthy living environment.

### RECOMMENDED USE

Osmo Wash and Care is especially suitable for cleaning and maintaining oiled and waxed wooden flooring. Furthermore, it is also recommended for furniture, doors, wall and ceiling panelling.

### INGREDIENTS

Based on natural plant oils; 5-15% plant soaps (anionic tensides); <5% non-ionic tensides; care components, suspending agent.  
Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 1.01-1.03 g/cm<sup>3</sup>  
Odour: faint/mild, after drying odourless  
pH value at 20°C: 10.9

### STORAGE

Up to 5 years and longer if container is kept dry, closed tightly and stored at temperatures between 5 and 35°C. Do not expose to frost during transport!

### SURFACE PREPARATION

To remove loose dirt, we recommend dry cleaning with Osmo Dust-Mop, a conventional vacuum cleaner or broom.

### METHODS OF APPLICATION

Manual:

Wash and Care is ideally used with Osmo Opti-Set (Micro-Mop Plush). Add Osmo Wash and Care to water. Clean the floor with a damp (not wet) mop and wipe dry immediately. When applied regularly, the surface becomes resistant to dirt and signs of wear.

Mechanical:

Spread the diluted Wash and Care solution with a pump sprayer. Loosen dirt with a single disc machine, e.g. Osmo FloorXcenter, and a white pad. Immediately, mop away or remove with a round Osmo Microfibre Pad for machines.

### COVERAGE

1 capful of Wash and Care per litre water.  
For higher levels of soiling or for mechanical applications, dosage can be increased up to a mixing ratio of 1:1.

### NOTE

To specifically remove especially tough stains and to occasionally, intensively refresh waxed or oiled floors, we recommend using our tried and trusted Osmo Liquid Wax Cleaner, which is based on natural plant oils and waxes (undiluted use with Osmo Opti-Set Active Fibre Cloth). For a complete renovation, we recommend Osmo Polyx®-Oil.

For use with Osmo FloorXcenter:

White pad: for loosening everyday household dirt and stains.



Brush ring: for removing coarse dirt even in pores.  
Red pad: for removing especially tough stains. (Re-oiling is recommended.)  
After loosening dirt, remove dirt with the Microfibre Pad. Repeat process until the complete area is clean. For detailed information, please consult the Product Information for FloorXcenter.  
Strong mechanical cleaning applications (e.g. single disc machine with a red pad) also remove soluble wax and oil remnants. After drying, one coat of an Osmo Polyx®-Oil must be applied thinly to flooring.

#### CAUTION

Keep out of reach of children.  
If medical advice is needed, have product container or label at hand.

#### DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

#### COLOUR TONES

8016 Clear

#### CAN SIZES

0.75 L; 5.0 L; 25 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 03/16



## LIQUID WAX CLEANER

Clean and refresh in one step!



3029  
Clear



3087 White  
Transparent



### PRODUCT DESCRIPTION

Clear or transparent wax-based care product for occasionally refreshing interior wooden flooring with Polyx®-Oil surfaces, furniture as well as other interior oiled and waxed wood surfaces.

Through appropriate care, the surface is provided with the natural, safe hard waxes (carnauba and candelilla waxes). The floor stays hard-wearing without forming a film.

### RECOMMENDED USE

Osmo Liquid Wax Cleaner / Spray is ideal for removing tough stains, e.g. grease or shoe polish, and best suited for refreshing all surfaces treated with Osmo Polyx®-Oil.

### INGREDIENTS

Based on natural plant waxes (carnauba wax, candelilla wax); paraffin, aliphatic hydrocarbons (>30%).

Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.77-0.8 g/cm<sup>3</sup>

Viscosity: >30s DIN EN ISO 2431/3 mm, viscid

Odour: faint/mild, odourless after drying

Flash point: >60°C acc. DIN EN ISO 2719

### Storage

Up to 5 years and longer if container is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

### SURFACE PREPARATION

Wood surface must be dust-free and dry. For this purpose generally a dust mop, a mop or a vacuum cleaner is suitable. For simple cleaning and maintenance, Osmo Opti-Set (Dust-Mop, Micro-Mop Plush and an Active Fibre Cloth) is highly recommended. For

cleaning high-traffic and very dirty flooring, e.g. in public spaces, use Osmo Micro-Mop (water mixed with Osmo Wash and Care) and buffed dry afterwards.

### METHODS OF APPLICATION

Manual application:

For removing stains and for intensive maintenance, please use Osmo Liquid Wax Cleaner with our Active Fibre Cloth (approx. 2 teaspoons per m<sup>2</sup>).

Rub away especially tough stains with Osmo Liquid Wax Cleaner with a cloth or a Scotchpad.

Mechanically application:

Apply Osmo Liquid Wax Cleaner with a single disc machine and a white pad (approx. 2 teaspoons per m<sup>2</sup>). Spread Liquid Wax Cleaner on the surface evenly and massage in.

Should streaks appear, either turn the pad over or use a new pad, also see FloorXCenter description.

To achieve a higher gloss level, polish the dried surface with a white pad.

### CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

### DRYING TIME

Approx. 30-40 minutes (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying.

### COVERAGE

Product coverage of Osmo Liquid Wax Cleaner / Spray strongly depends on the absorption and on the amount of dirt and stains on the substrate. (1 litre of care product covers approx. 80-100 m<sup>2</sup>, 2 teaspoons for approx. 1 m<sup>2</sup>).



## NOTE

By applying hard waxes (carnauba and candelilla waxes) regularly, the floor is refreshed, and resistance to cracks and wear is improved.

However, it is absolutely necessary to return the required oil components of Polyx®-Oil to the floor within the course of one year.

Only apply thinly; otherwise footprints may appear.

Please use only Osmo Liquid Wax Cleaner White on white subsurfaces.

On especially high traffic areas, re-apply Osmo Polyx®-Oil to the cleaned area.

## CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Safety data sheet available on request.

## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

3029 Clear

3087 White Transparent

## SIZES

Liquid Wax Cleaner: 0.5 L; 1 L; 10 L

Liquid Wax Cleaner White: 1 L; 10 L

Liquid Wax Cleaner Spray Clear: 400 ml spray (not white transparent)

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 03/16